

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-12A-LLH110A-S17



(Full size images available on web site)

New SL-LCD-12A-RTOUCH-2 Added HDMI!

Type:

- Panel PC
- **Screen:**
 - 12" 5-Wire Resistive, Native Resolution: 800 x 600, Front Panel Rating: IP65 / NEMA4
- **Mounting:** Bezel Mounting Hardware Included, Suitable for Mounting in Cut-Out

Motherboard:

- Featuring Intel H110 Chipset and 7th and 6th Gen Core i7/i5/i3 (LGA1151) processor
- **Long Production Cycle Motherboard (Through Q1 2030)**
- **No Available Slots**
- **LAN:** 2x Ports (1GbE + 1GbE)
- **Video:** VGA + DisplayPort + HDMI
- **Audio:** Intel HD Audio
- **Ports:**
 - 4x USB 2.0 Ports (2 Front, 2 Internal Headers)
 - 4x USB 3.2 Gen 1 Ports (4 Rear)
 - 4x COM Ports (1 RS232 Rear, 2 RS232 Internal Headers, 1 RS232/422/485 Rear)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

Configuration summary:

- **Processor:** G4400 - 3.3GHz Intel Pentium Dual Core - 3MB Cache, HD Graphics 510 (54W) (ERM) or Better
- **Memory:** 8GB DDR4 2666MHz SODIMM

RAM

- **Hard Drive:** 250GB SSD SATA 6.0Gb/s 560/530MB/s 2.5" - Samsung 870 EVO
- **Power Supply:** 160w output, 12v input DC-DC Power Supply - AC Adapter Included
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2030

Supported CPU

- Number of Processors: 1
- Processor Type: 7th and 6th Gen Core i7/i5/i3 (LGA1151)

Chipset

- Chipset: Intel H110 Chipset

Memory

- Memory Type: SO DIMM DDR4 2133MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 32GB

On Board Audio

- Audio Type: Intel HD Audio

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: VGA + DisplayPort + HDMI
- VGA Port Out: 1
- Display Port Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE
- LAN Chipset: Intel i219V
- Second LAN Chipset: Intel i210AT

Display Specifications

Display

- Screen Size (inches): 12
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Aspect Ratio: 4 : 3
- Native Display Resolution: 800 x 600
- Brightness (nits): 400
- Screen Refresh Rate: 60Hz
- Display Area (H): 246mm
- Display Area (V): 184.50mm
- Aspect Ratio: 4 : 3
- DisplayColors: 16.2 M
- Contrast Ratio: 600:1
- Backlight: LED
- Viewing Angle(U) : 65
- Viewing Angle(D) : 75
- Viewing Angle(L) : 80
- Viewing Angle(R) : 80

Connectivity

- HDMI In: 1
- Display Port In: 1
- Touchscreen Interface USB Port (Front): 1

Mounting Options

- Mounting Options: Bezel Mounting Hardware Included, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width:
- Height:
- Depth:

- Wireless LAN: No Integrated WLAN

Drive Interface

- SAS 6G Ports: 4

Expansion Slots

- PCI Express x16 Slots On Motherboard: 1

Mini PCIe

- mini PCIe
- mSATA
- USB and PCIe signals (Internal)
- half and/or full size mini PCIe card: full/half size

Rear IO

- USB 3.2 Gen 1 Type A Ports (on IO): 4
- Serial (Rear IO): 1
- Serial 232/422/485 Ports: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- Serial (via Headers): 2
- LVDS
- TPM Support: Via 2.0 Header

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (32-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- SL-Windows 10PRO to 7PRO 32-bit
- SL-Windows 10PRO to 7PRO 64-bit
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows 8.1 (32-bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (32-bit)
- Windows 8.1 Pro (64-bit)
- Windows Embedded 8 (32-bit)
- Windows Embedded 8 (64-bit)
- Windows 10 Home (32 Bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (32 Bit)
- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 32bit

- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Unboxed Weight: 9lbs
- Shipping Weight: 25lbs

Environmental

- MTBF: 50000hours
- Maximum Operating Temperature: 80C
- High Humidity: 90%
- Low Humidity: 8%
- Storage Temp (High): 80C
- Storage Temp (Low): -30C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 8%

Power

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 12Watts

Compliance of Component

- CE
- CCC

Warranty

- Warranty: 1 year

Other

- Built-in Chassis Power Supply: Wide Voltage Input (9-36VDC)

- Features:

Industrial Display

- Screen Size: 12"
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Native Display Resolution: 800 x 600
- Brightness (nits): 400
- Wide Voltage Input (9-36VDC)

- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value
- Windows 10 IoT Ent
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

Compliance of Component

- UL
- CE
- RoHS
- FCC

Other Features

- Other Features:
 - 1 x PCIe 3.0 x16 (in x16) slot
 - 1 (half/full size, supports PCIe x1 and USB device)
 - 1 (full size, shared SATA and USB device)

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year

Chassis Specifications:

General

- Form Factor: Micro PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX

Expansion

- Internal 2.5" Bays: 1
- Serial Port Punchouts: 2
- Parallel Port Punchouts: 1
- Antennae Punchout: 2

Front Ports

- USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 1

Physical

- Depth: 8.27"
- Depth (Inches): 8.27
- Width: 7.60"
- Height: 2.60"
- Shipping Box - Depth: 13"
- Shipping Box - Width: 9"
- Shipping Box - Height: 5"
- Shipping Weight: 8lbs

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: AC/DC Power Adapter Included



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525