

Microbox PC Embedded PC

Configuration Number: BASE CONFIG
SL-EB-N2930-J



(full size images available on web site)

Completely Fanless

Type:

- Microbox PC
- Dimension: 142mm x 185mm x 48mm

Motherboard:

- Featuring Intel Celeron SoC and Intel Celeron N2930 Processor (1.83GHz Quad Core, Burst 2.16GHz) TDP 7.5W
- **Long Production Cycle Motherboard (Through Q1 2029)**
- **LAN:** 2x Ports (1GbE (10/100/1000))
- **WiFi:** Integrated Realtek 802.11 b/g/n Wireless LAN/Bluetooth 4.0 - Removable Under Networking Section
- **Video:** VGA + DVI-D
- **Audio:** Realtek ALC662 HD Audio
- **Ports:**
 - 5x USB 2.0 Ports (2 Front, 3 Rear)
 - 1x USB 3.2 Gen 1 Port(1 Rear)
 - 4x COM Ports (2 RS232 Rear, 1 RS232 Internal Headers, 1 RS232/422/485 Internal Headers)

See specifications for more ports
- **Operating Temperature:** 0°C to 40°C (32°F to 104°F)

Configuration summary:

- **Memory:** 4GB DDR3L 1600MHz SODIMM RAM 1.35V
- **Hard Drive:** 120GB SSD SATA 6.0Gb/s, 500/320MB/s read/write (or greater)
- **Power Supply:** +9V ~ +24V DC-in jack
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: Proprietary
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2029
- Fanless

Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Celeron N2930 Processor (1.83GHz Quad Core, Burst 2.16GHz) TDP 7.5W

Chipset

- Chipset: Intel Celeron SoC

Memory

- Memory Type: SO DIMM DDR3 1333MHz
- Memory Type: Non-ECC
- DIMMS: 1
- Maximum Memory: 8GB

On Board Audio

- Audio Type: Realtek ALC662 HD Audio

On Board Video

- Video Chipset: Intel HD Graphics
- Video on IO: VGA + DVI-D
- VGA Port Out: 1
- DVI-D Out: 1

LAN

- LAN Ports: 2
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Realtek RTL8111G
- Second LAN Chipset: Realtek RTL8111G
- Wireless LAN: Integrated Realtek 802.11 b/g/n
Wireless LAN/Bluetooth 4.0 - Removable Under Networking Section

Drive Interface

- SATA II Ports (3GB): 1

Expansion Slots

- mini PCIe

Chassis Specifications:

General

- Form Factor: Embedded PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Slide Rails: Optional

Expansion

- Internal 2.5" Bays: 1
- Serial Port Punchouts: 2

Front Ports

- USB 2.0 Ports (Front): 2
- Front Audio Ports: 1

Physical

- Depth: 142mm
- Width: 185mm
- Height: 48mm
- Shipping Box - Depth: 118mm
- Shipping Box - Width: 250mm
- Shipping Box - Height: 295mm
- Shipping Weight: 7lbs

Power

- Built-in Chassis Power Supply: +9V ~ +24V DC-in jack

- mSATA
- USB and PCIe signals (Internal)
- half and/or full size mini PCIe card: full size

M.2 Slot Specs

Rear IO

- USB 2.0 Ports (on IO): 3
- USB 3.2 Gen 1 Type A Ports (on IO): 1
- Serial (Rear IO): 2
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 2
- Serial (via Headers): 1
- Serial 232/422/485 Ports: 1

Management Features

- Watch Dog

Environmental

- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- Windows 7 PRO (FES) DGS 32-BIT
- Windows 7 PRO (FES) DGS 64-BIT
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows Embedded 8 (32-bit)
- Windows Embedded 8 (64-bit)
- Windows 8.1 (32-bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (32-bit)
- Windows 8.1 Pro (64-bit)
- Windows 10 Home (32 Bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (32 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 IoT Entry 32-bit
- Windows 10 IoT Entry
- Windows 10 IoT Entry 32-bit 2019 LTSC
- Windows 10 IoT Entry 2019 LTSC
- SL-Windows 11PRO to 10PRO 32bit
- SL-Windows 11PRO to 10PRO 64bit
- LINUX Ubuntu Desktop

Compliance of Component

- UL
- CE
- FCC
- CB
- CCC

Warranty of Component

- Motherboard Warranty: 1 Year

Other Features

- Other Features:
12V AC/DC Adapter, Power Cord, Wall bracket,
DIN Rail Clip Included

*USB 2.0 Header are used for the front USB Ports



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525