

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-15AWHD-J5040-S19



Type:

- Panel PC
- **Screen:**
 - 15.6" 5-Wire Resistive, Native Resolution: 1920 x 1080, Front Panel Rating: IP65 / NEMA4
- **Mounting:** Bezel Mounting Hardware Included, Suitable for Mounting in Cut-Out

Motherboard:

- Featuring Intel Pentium SoC and Intel Pentium Quad-Core Processor J5040 (up to 3.2 GHz)
- **Low Profile Slots:**
 - 1 - PCIe x1
- **LAN:** 1x Ports (1GbE (10/100/1000))
- **Video:** VGA + DVI-D + HDMI
- **Audio:** Realtek ALC892
- **Ports:**
 - 5x USB 2.0 Ports (2 Front, 2 Rear, 1 Internal Headers)
 - 4x USB 3.2 Gen 1 Ports (2 Rear, 2 Internal Headers)
 - 1x COM Port (RS232 Internal Headers)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 50°C (32°F to 122°F)

Configuration summary:

- **Memory:** 8GB DDR4 2666MHz SODIMM RAM
- **Hard Drive:** 250GB SSD SATA 6.0Gb/s 560/530MB/s 2.5" - Samsung 870 EVO
- **Power Supply:** 90w output, 12v input DC-DC Power Supply - AC Adapter Included

- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX

Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Pentium Quad-Core Processor J5040 (up to 3.2 GHz)

Chipset

- Chipset: Intel Pentium SoC

Memory

- Memory Type: DDR4 2400MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 8GB

On Board Audio

- Audio Type: Realtek ALC892

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: VGA + DVI-D + HDMI
- VGA Port Out: 1
- DVI-D Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 1
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Realtek RTL8111H
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 4

Expansion Slots

- PCI Express x1 Slots On Motherboard: 1

M.2 Slot Specs

Display Specifications

Display

- Screen Size (inches): 15.6
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Aspect Ratio: 16:9
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 250
- Screen Refresh Rate: 60Hz
- Display Area (H): 344.16mm
- Display Area (V): 193.59mm
- Aspect Ratio: 16:9
- DisplayColors: 16.2 M
- Contrast Ratio: 400:1
- Backlight: LED
- Viewing Angle(U) : 70
- Viewing Angle(D) : 70
- Viewing Angle(L) : 60
- Viewing Angle(R) : 60

Connectivity

- VGA Port In: 1
- DVI-I In: 1
- HDMI In: 1
- Touchscreen Interface USB Port (Front): 1

Mounting Options

- Mounting Options: Bezel Mounting Hardware Included, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width:
- Height:
- Depth:
- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Unboxed Weight: 10lbs
- Shipping Weight: 30lbs

Environmental

- M.2 Slot #1 Specs
- PCIe Signal
- 2230 - 22 mm x 30 mm.

Rear IO

- PS/2 Mouse on IO
- PS/2 Keyboard on IO
- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- SPDIF Connector: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 3
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 1
- FAN Connectors: 2
- Audio on Headers

Environmental

- Operating Temperature: 0°C to 50°C (32°F to 122°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Entry 2019 LTSC
- Windows 10 IoT 2021 LTSC Entry
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 IoT 2024 LTSC Entry
- LINUX Ubuntu Desktop

Compliance of Component

- CE
- FCC

Other Features

- Other Features:
 - *USB3_0_1 is shared with USB_0_1.
- Motherboard Warranty: 1 Year

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- High Humidity: 90%
- Low Humidity: 8%
- Storage Temp (High): 60C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 8%

Power

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 13Watts

Compliance of Component

- CE
- RoHS
- FCC
- CB
- CCC

Warranty

- Warranty: 1 year

Other

- Features:

Industrial Display

- Screen Size: 15.6"
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 250

Chassis Specifications:

General

- Form Factor: Embedded PC
- Color: Black
- Material: Metal/Steel

- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX

Expansion

- Low Profile Slots: 1
- Max Card Depth: 7.5"
- Internal 2.5" Bays: 2
- Serial Port Punchouts: 2
- Parallel Port Punchouts: 1

Front Ports

- USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 2

Physical

- Depth: 8.30"
- Depth (Inches): 8.27
- Width: 8"
- Height: 3.50"
- Shipping Box - Depth: 150mm
- Shipping Box - Width: 380mm
- Shipping Box - Height: 27mm
- Shipping Weight: 13lbs

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: Power Adapter
Included



Simplifying Computing™

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525