

## 2U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG  
SL-2U-LLW480M-WD



### TPM Support: 2.0 Module Included

#### Type:

- 2U Rack Mount Server
- Depth: 18", Max Card Depth: 12.25", Locking Front Bezel

#### Motherboard:

- Featuring Intel W480 Chipset and 10th Gen Intel Core i9, i7, i5, i3/Pentium/Celeron, Intel Xeon W-1200 processor
- **Long Production Cycle Motherboard (Through Q2 2030)**
- **Low Profile Slots:**
  - 1 - PCIe x16
  - 1 - PCIe x8
  - 1 - PCIe x4
- **LAN:** 2x Ports (1GbE + 1GbE)
- **RAID:** 0,1,5,10
- **Video:** VGA + DVI-I + DisplayPort
- **Audio:** Realtek ALC888S HD Audio
- **Ports:**
  - 6x USB 2.0 Ports ( 6 Internal Headers )
  - 4x USB 3.2 Gen 2 Ports ( 4 Rear )
  - 1x USB 3.2 Gen 2 Type-C Port ( 1 Internal Headers )
  - 2x COM Ports (RS232 Internal Headers)
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

#### Configuration summary:

- **Processor:** i3-10100 - 3.6GHz (up to 4.3GHz) Intel Quad-Core (4 cores) CPU - 6MB Cache, UHD Graphics 630 (65W)

- **Memory:** 8GB DDR4 3200MHz RAM
- **Hard Drive:** 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980
- **Power Supply:** 400W Power Supply
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

## Technical Specifications

### MotherBoard Specifications:

#### Motherboard Model

- Motherboard Type: MicroATX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q2 2030

#### Supported CPU

- Number of Processors: 1
- Processor Type: 10th Gen Intel Core i9, i7, i5, i3/Pentium/Celeron, Intel Xeon W-1200

#### Chipset

- Chipset: Intel W480 Chipset

#### Memory

- Memory Type: DDR4 2666MHz
- Memory Type: ECC Unbuffered
- DIMMS: 4
- Maximum Memory: 128GB

#### On Board Audio

- Audio Type: Realtek ALC888S HD Audio

#### On Board Video

- Video Chipset: ASPEED AST2500 BMC
- Video on IO: VGA + DVI-I + DisplayPort
- VGA Port Out: 1
- DVI-D Out: 1
- Display Port Out: 2

#### LAN

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE
- LAN Chipset: Intel i210AT
- Second LAN Chipset: Intel i219LM
- Wireless LAN: No Integrated WLAN

#### Drive Interface

### Chassis Specifications:

#### General

- Form Factor: 2U Rackmount
- Color: Black & Silver
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: ATX
- Slide Rails: Optional

#### Expansion

- Low Profile Slots: 7
- Max Card Depth: 12.25"
- External 5.25" Bays: 1
- Internal 3.5" Bays: 2
- External 3.5" Bays: 1
- Internal 2.5" Bays: 1

#### Front Ports

- USB 3.2 Ports (Front): 2

#### Cooling System

- Maximum Fan Count: 3
- Included Fans: 1

#### Physical

- Depth: 18"
- Depth (Inches): 18
- Width: 16.90"
- Height: 3.50"
- Shipping Box - Depth: 20"
- Shipping Box - Width: 40"
- Shipping Box - Height: 40"
- Shipping Weight: 35lbs

#### Compliance of Component

- RoHS

#### Other Features

- Chassis Warranty: 1 Year

- SATA III Ports (6GB): 4
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

#### **Expansion Slots**

- PCI Express x16 Slots On Motherboard: 1
- PCI Express x8 Slots On Motherboard: 1
- PCI Express x4 Slots On Motherboard: 1

#### **M.2 Slot Specs**

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCIe Signal
- 22110 - 22 mm x 110 mm.
- 2280 - 22 mm x 80 mm.

#### **Rear IO**

- USB 3.2 Gen 2 Type A Ports (on IO): 4

#### **Headers**

- USB 2.0 Ports (on Headers): 6
- USB 3.2 Gen 2 Type-C (on Headers): 1
- Serial (via Headers): 2
- FAN Connectors: 5
- Audio on Headers
- Chassis Intrusion
- TPM Support: 2.0 Module Included

#### **Management Features**

- AMT
- vPRO
- Watch Dog

#### **Environmental**

- Operating Temperature: 0°C to 60°C (32°F to 140°F )
- High Humidity: 85%
- Low Humidity: 10%

#### **Operating System Support**

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)

- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- Windows Server 2019 Std
- Windows Server 2022 STD
- RED HAT Enterprise LINUX WORKSTATION STANDARD
- RED HAT Enterprise LINUX SERVER BASIC
- RED HAT Enterprise LINUX SERVER STANDARD
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

#### **Compliance of Component**

- CE
- RoHS
- FCC

#### **Other Features**

- Other Features:

##### **PCIE:**

- 1 PCI-E 3.0 x16,
- 1 PCI-E 3.0 x4 (in x8 slot),
- 1 PCI-E 3.0 x4

##### **M.2**

- 1 M.2 M-Key SATA/PCI-E 3.0 x4, 2280/22110
- 1 M.2 E-Key CNVi/PCI-E 3.0 x1, 2230

##### **Management Software**

- AMT, IPMI (Intelligent Platform Management Interface) v2.0 with KVM support, SUM, SuperDoctor® 5, vPro, Watchdog

\* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year



www.superlogics.com  
Phone: 1-508-650-9500

sales@superlogics.com  
Fax: 1-508-650-9525