uperLogics

4U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG SL-4U-LLQ370J-HA





TPM Support: 2.0 Module Included

Type:

- 4U Rack Mount Industrial PC
- Depth: 17.70", Max Card Depth: 12.28", Locking Front Bezel

Motherboard:

- Featuring Intel Q370 Chipset and 8th and 9th Gen Core i7/i5/i3 (LGA1151) processor
- Long Production Cycle Motherboard (Through Q2 2033)
- Full Height Slots:
 - 2 PCIe x16
 - 1 PCIe x4
 - 1 PCIe x1
 - 2 PCI
- LAN: 2x Ports (1GbE + 1GbE)
- **RAID:** 0,1,5,10
- **Video:** VGA + HDMI + DVI-I + DisplayPort
- Audio: Realtek ALC662 HD Audio
- Ports:

4x USB 2.0 Ports (2 Front, 2 Internal Headers)

4x USB 3.2 Gen 1 Ports (2 Rear, 2 Internal Headers)

4x USB 3.2 Gen 2 Ports (4 Rear) 10x COM Ports (8 RS232 Internal Headers, 1 RS232/422/485 Rear, 1 RS232/422/485 Internal Headers) See specifications for more ports

• Operating Temperature: 0°C to 60°C (32°F to 140°F)

Configuration summary:

- Processor: G4900 3.1GHz Intel Celeron CPU - Dual Core, 2MB Cache, UHD Graphics 610 (54W) (ERM) - or Better
- Memory: 8GB DDR4 3200MHz RAM
- Hard Drive: 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980
- **Power Supply:** 400W Power Supply
- Operating System: Not Included -
- Warranty: One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: ATX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q2 2033

Supported CPU

- Number of Processors: 1
- Processor Type: 8th and 9th Gen Core i7/i5/i3 (LGA1151)

Chipset

• Chipset: Intel Q370 Chipset

Memory

- Memory Type: DDR4 2666MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 128GB

On Board Audio

• Audio Type: Realtek ALC662 HD Audio

On Board Video

- Video Chipset: Supported by CPU depends on CPU selected
- Video on IO: VGA + HDMI + DVI-I + DisplayPort
- VGA Port Out: 1
- DVI-D Out: 1
- Display Port Out: 1
- HDMI Out: 1

Chassis Specifications:

General

- Form Factor: 4U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: ATX
- Redundant Power Supply Capable
- Slide Rails: Optional

Expansion

- Full Height Slots: 7
- Max Card Depth: 12.28"
- External 5.25" Bays: 3
- Internal 3.5" Bays: 2
- External 3.5" Bays: 1

Front Ports

• USB 2.0 Ports (Front): 2

Cooling System

- Maximum Fan Count: 2
- Included Fans: 1

Physical

- Depth: 17.70"
- Depth (Inches): 17.7
- Width: 19"
- Height: 7"
- Shipping Box Depth: 26"
- Shipping Box Width: 23"
- Shipping Box Height: 12"

LAN

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE
- LAN Chipset: Intel i211AT
- Second LAN Chipset: Intel i219LM
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 5
- RAID
- RAID Type: Software RAID
- RAID Levels Supported on Motherboard: 0, 1, 5, 10

Expansion Slots

- PCI Express x16 Slots On Motherboard: 2
- PCI Express x4 Slots On Motherboard: 1
- PCI Express x1 Slots On Motherboard: 1
- PCI Slots (Conventional 32-Bit): 2

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCle Signal
- 22110 22 mm x 110 mm.
- 2242 22 mm x 42 mm.
- 2260 22 mm x 60 mm.
- 2280 22 mm x 80 mm.

Rear IO

- USB 3.2 Gen 1 Type A Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 4
- Serial 232/422/485 Ports: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 8
- Serial 232/422/485 Ports: 1
- SPDIF Connector: 1
- FAN Connectors: 3
- Audio on Headers
- TPM Support: 2.0 Module Included

Management Features

- AMT
- Watch Dog

Environmental

 Operating Temperature: 0°C to 60°C (32°F to 140°F) • Shipping Weight: 45lbs

Other Features

Chassis Warranty: 1 Year

- High Humidity: 95%
- Low Humidity: 10%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

Compliance of Component

- CE
- RoHS
- FCC

Other Features

• Features:

4 x 288-pin UDIMM Unbuffered Dual Channel DDR4-2666 up to 128GB Total * Core i3, Pentium, and Celeron can only support DDR4-2400 up to 64GB Total

1x PCI-E 3.0 x16 Slot (by 16-lane)

1x PCI-E 3.0 x16 Slot (by 8-lane)

1x PCI-E x4 Slot

1x PCI-E x1 Slot

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers

• Motherboard Warranty: 1 Year



www.superlogics.comsales@superlogics.comPhone: 1-508-650-9500Fax: 1-508-650-9525