

Desktop PC Desktop

Configuration Number: BASE CONFIG
SL-DK-LLH310I-IM



Type:

- Desktop PC
- Dimension: 193mm x 76mm x 225mm

Motherboard:

- Featuring Intel H310 Chipset and 8th and 9th Gen Core i7/i5/i3 (LGA1151) processor
- **Long Production Cycle Motherboard (Through Q1 2025)**
- **No Available Slots**
- **LAN:** 2x Ports (1GbE + 1GbE)
- **Video:** VGA + DisplayPort + HDMI
- **Audio:** Realtek ALC887 codec
- **Ports:**
 - 2x USB 2.0 Ports (2 Internal Headers)
 - 4x USB 3.2 Gen 1 Ports (4 Rear)
 - 4x COM Ports (2 RS232 Rear, 2 RS232 Internal Headers)
 - 1x Front Audio Port
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

Configuration summary:

- **Processor:** G4900 - 3.1GHz Intel Celeron CPU - Dual Core, 2MB Cache, UHD Graphics 610 (54W) (ERM) - or Better
- **Memory:** 8GB DDR4 2666MHz SODIMM RAM
- **Hard Drive:** 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980
- **Power Supply:** 150W Internal PSU
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2025

Supported CPU

- Number of Processors: 1
- Processor Type: 8th and 9th Gen Core i7/i5/i3 (LGA1151)

Chipset

- Chipset: Intel H310 Chipset

Memory

- Memory Type: SO DIMM DDR4 2400MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 32GB

On Board Audio

- Audio Type: Realtek ALC887 codec

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: VGA + DisplayPort + HDMI
- VGA Port Out: 1
- Display Port Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE
- LAN Chipset: Intel GbE LAN chip
- Second LAN Chipset: Intel GbE LAN chip
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 4

Expansion Slots

- PCI Express x16 Slots On Motherboard: 1

Mini PCIe

- mini PCIe
- mSATA

Chassis Specifications:

General

- Form Factor: Desktop PC
- Color: Black
- Material: Steel & Plastic
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX

Expansion

- Internal 2.5" Bays: 1

Front Ports

- USB 3.2 Ports (Front): 2
- Front Audio Ports: 1

Physical

- Depth: 193mm
- Depth (Inches): 7.6
- Width: 76mm
- Height: 225mm
- Shipping Box - Depth: 120mm
- Shipping Box - Width: 270mm
- Shipping Box - Height: 273mm
- Shipping Weight: 10lbs

Compliance of Component

- CE
- RoHS
- FCC

Other Features

- Features:
With a depth of less than 80mm, this system can easily be mounted behind a LCD monitor.
- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: 150W Internal PSU

- half and/or full size mini PCIe card: full size

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCIe Signal
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.

Rear IO

- USB 3.2 Gen 1 Type A Ports (on IO): 4
- Serial (Rear IO): 2
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 2
- Serial (via Headers): 2
- FAN Connectors: 2
- Audio on Headers
- TPM Support: 2.0 Module Included

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 95%
- Low Humidity: 5%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop
- LINUX Ubuntu Workstation
- Ubuntu Server Edition

Compliance of Component

- CE
- RoHS
- FCC

Other Features

- Other Features:
 - 1 x PCI Express x16 slot, running at x16

(PCIEX16)

(The PCIEX16 slot conforms to PCI Express 3.0 standard.)

- 1 x M.2 Socket 1 connector for an Intel® CNVi or PCIe wireless module (CNVi)
- 1 x full size Mini PCIe connector (MSATA_PCIE)

* The MSATA_PCIE slot shares bandwidth with the SATA3 2 connector. When an MSATA SSD is populated, the SATA3 2 connector becomes unavailable.

* The MSATA_PCIE connector can also be used as an MSATA connector.

(The Mini PCI Express slot conforms to PCI Express 2.0 standard.)

- Motherboard Warranty: 1 Year



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525