

## HMI Panel PC Panel PC

Configuration Number: BASE CONFIG  
SL-PPC-12AWHD-J6412-H-2LAN



**LCD requires 12VDC power supply (included), Separate Computer input is wide voltage input**

### Type:

- Fanless Panel PC
- **Screen:**
  - 11.6" Multi-Touch Projected Capacitive, Native Resolution: 1920 x 1080, Front Panel Rating: IP65 / NEMA4
- **Mounting:** Suitable for Mounting in Cut-Out

### Motherboard:

- Featuring Intel Celeron SoC and Intel Celeron J6412 Elkhart Lake Platform (Quad Core 2.0GHz/10W, Turbo 2.6GHz)
- **Long Production Cycle Motherboard (Through Q1 2036)**
- **LAN:** 2x Ports (2.5GbE (10/100/1000/2500))
- **WiFi:** Wireless AC
- **Video:** DisplayPort + HDMI
- **Audio:** Realtek ALC888S HD Audio
- **Ports:**
  - 1x USB 2.0 Port( 1 Front )
  - 1x USB 3.2 Gen 1 Port( 1 Front )
  - 1x USB 3.2 Gen 2 Port ( 1 Rear )

See specifications for more ports
- **Operating Temperature:** -20°C to 60°C (-4°F to 140°F)



### Configuration summary:

- **Memory:** 8GB DDR4 3200MHz SODIMM RAM

- **Hard Drive:** 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980
- **Power Supply:** Adapter : AC\_90~240V / DC\_12V/40W
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### Motherboard Model

- Motherboard Type: NUC (101x101 mm)
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2036
- Fanless

### Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Celeron J6412 Elkhart Lake Platform (Quad Core 2.0GHz/10W, Turbo 2.6GHz)

### Chipset

- Chipset: Intel Celeron SoC

### Memory

- Memory Type: SO DIMM DDR4 3200MHz
- Memory Type: Non-ECC
- DIMMS: 1
- Maximum Memory: 32GB

### On Board Audio

- Audio Type: Realtek ALC888S HD Audio

### On Board Video

- Video Chipset: Intel UHD Graphics for 10th Gen Intel Processors
- Video on IO: DisplayPort + HDMI
- Display Port Out: 1
- HDMI Out: 2

### LAN

- LAN Ports: 2
- LAN Type: 2.5GbE (10/100/1000/2500)
- LAN Chipset: Intel I225-V 2.5GbE Ethernet
- Second LAN Chipset: Intel i225-V 2.5GbE Ethernet

## Display Specifications

### Display

- Screen Size (inches): 11.6
- Touch Type: Multi-Touch Projected Capacitive
- Front Panel Rating: IP65 / NEMA4
- Aspect Ratio: 16 : 9
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 300
- Screen Refresh Rate: 60Hz
- Display Area (H): 255mm
- Display Area (V): 145mm
- Aspect Ratio: 16 : 9
- DisplayColors: 16.7 M
- Contrast Ratio: 1000:1
- Backlight: LED
- Viewing Angle(U) : 178
- Viewing Angle(D) : 178
- Viewing Angle(L) : 178
- Viewing Angle(R) : 178

### Connectivity

- VGA Port In: 1
- DVI-D In: 1
- HDMI In: 1
- Touchscreen Interface USB Port (Front): 1

### Mounting Options

- Mounting Options: VESA 75mm x 75mm, VESA 100mm x 100mm, Side Mounting Brackets Included, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

### Physical

- Width:
- Height:
- Depth:

- Wireless LAN: Wireless AC

### **M.2 Slot Specs**

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- M.2 SATA SSD
- PCIe Signal
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.

### **Rear IO**

- USB 3.2 Gen 2 Type A Ports (on IO): 1

### **Headers**

- USB 2.0 Ports (on Headers): 1
- USB 3.2 Gen 1 Ports (on Headers): 1
- FAN Connectors: 1

### **Management Features**

- TPM Support: TPM via Intel Platform Trust Technology

### **Environmental**

- Operating Temperature: -20°C to 60°C (-4°F to 140°F )
- High Humidity: 95%
- Low Humidity: 10%

### **Operating System Support**

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 IoT 2021 LTSC Entry
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 11 IoT 2024 LTSC Entry
- LINUX Ubuntu Desktop

### **Compliance of Component**

- UL
- CE
- RoHS
- FCC
- CB
- CCC

### **Warranty of Component**

- Motherboard Warranty: 1 Year

- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Unboxed Weight: 5lbs
- Shipping Weight: 9lbs

### **Environmental**

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- Low Operating Temp: 0C
- High Humidity: 90%
- Low Humidity: 5%
- Storage Temp (High): 60C
- Storage Temp (Low): -20C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 5%

### **Power**

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 10Watts

### **Compliance of Component**

- CE
- CCC

### **Warranty**

- Warranty: 1 year

## Chassis Specifications:

### **General**

- Form Factor: NUC Box

- Front Facing I/O
- Color: Black
- Material: Steel & Plastic
- Material Thickness: 1mm

#### **Front Ports**

- USB 2.0 Ports (Front): 1
- USB 3.2 Ports (Front): 1
- USB 3.2 Gen 2 Type-C (Front): 2
- Front Audio Ports: 1

#### **Physical**

- Depth: 109.20mm
- Depth (Inches): [Click Available Downloads Tab >](#)  
Mechanical Drawings.
- Width: 125mm
- Height: 44.50mm
- Shipping Box - Depth:
- Shipping Box - Width:
- Shipping Box - Height:
- Shipping Weight: 2lbs

#### **Power**

- Built-in Chassis Power Supply: Adapter :  
AC\_90~240V / DC\_12V/40W



[www.superlogics.com](http://www.superlogics.com)  
Phone: 1-508-650-9500

[sales@superlogics.com](mailto:sales@superlogics.com)  
Fax: 1-508-650-9525