

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-13AWHD-N2930-1LAN-AC



Type:

- Fanless Panel PC
- **Screen:**
 - 13.3" Multi-Touch Projected Capacitive, Native Resolution: 1920 x 1080, Front Panel Rating: Not Rated
- **Mounting:** Suitable for Mounting in Cut-Out

Motherboard:

- Featuring Intel Celeron SoC and Intel Celeron N2930 Processor (1.83GHz Quad Core, Burst 2.16GHz) TDP 7.5W
- **Long Production Cycle Motherboard (Through Q1 2029)**
- **LAN:** 1x Ports (1GbE (10/100/1000))
- **WiFi:** Wireless AC
- **Video:** HDMI
- **Audio:** Onboard Audio
- **Ports:**
 - 2x USB 2.0 Ports (2 Rear)
 - 1x USB 3.2 Gen 1 Port(1 Front)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 35°C (32°F to 95°F)

Configuration summary:

- **Memory:** 4GB DDR3L 1600MHz SODIMM RAM 1.35V
- **Hard Drive:** 256GB mSATA SSD SATA 6.0Gb/s, 550/500MB/s read/write (or greater)
- **Power Supply:** 9V - 24V DC In Jack
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: NUC (101x101 mm)
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2029
- Fanless

Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Celeron N2930 Processor (1.83GHz Quad Core, Burst 2.16GHz) TDP 7.5W

Chipset

- Chipset: Intel Celeron SoC

Memory

- Memory Type: SO DIMM DDR3 1333MHz
- Memory Type: Non-ECC
- DIMMS: 1
- Maximum Memory: 8GB

On Board Audio

- Audio Type: Onboard Audio

On Board Video

- Video Chipset: Supported by CPU - see Embedded CPU Information
- Video on IO: HDMI
- HDMI Out: 2

LAN

- LAN Ports: 1
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Intel 82574L
- Wireless LAN: Wireless AC

Expansion Slots

- mSATA
- half and/or full size mini PCIe card: full size

M.2 Slot Specs

Rear IO

- USB 2.0 Ports (on IO): 2

Display Specifications

Display

- Screen Size (inches): 13.3
- Touch Type: Multi-Touch Projected Capacitive
- Aspect Ratio: 16 : 9
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 220
- Screen Refresh Rate: 60Hz
- Display Area (H): 293.76mm
- Display Area (V): 165.24"
- Aspect Ratio: 16 : 9
- DisplayColors: 16.7 M
- Contrast Ratio: 1000:1
- Backlight: LED
- Viewing Angle(U) : 178
- Viewing Angle(D) : 178
- Viewing Angle(L) : 178
- Viewing Angle(R) : 178

Connectivity

- HDMI In: 1
- Display Port In: 1
- Touchscreen Interface USB Port (Front): 1

Mounting Options

- Mounting Options: VESA 75mm x 75mm, VESA 100mm x 100mm, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width:
- Height:
- Depth:
- Depth (Inches): Click Available Downloads Tab > Mechanical Drawings.
- Unboxed Weight: 6lbs
- Shipping Weight: 11lbs

Environmental

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- High Humidity: 90%
- Low Humidity: 5%
- Storage Temp (High): 60C

Headers

- USB 3.2 Gen 1 Ports (on Headers): 1

Environmental

- Operating Temperature: 0°C to 35°C (32°F to 95°F)
- High Humidity: 95%
- Low Humidity: 10%

Operating System Support

- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- Windows 7 PRO (FES) DGS 32-BIT
- Windows 7 PRO (FES) DGS 64-BIT
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows 10 IoT 2021 LTSC Entry
- SL-Windows 11PRO to 10PRO 32bit
- SL-Windows 11PRO to 10PRO 64bit
- LINUX Ubuntu Desktop

Compliance of Component

- CE
- RoHS
- FCC

Warranty of Component

- Motherboard Warranty: 1 Year

- Storage Temp (Low): -20C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 5%

Power

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 10Watts

Compliance of Component

- RoHS

Warranty

- Warranty: 1 year

Other

- Built-in Chassis Power Supply: 9-36VDC Power Input
- Features:
13.3" Open Frame Full HD Touch Widescreen -
Mounting ears not removable

Display Specifications

- Display
- Screen Size: 13.3"
- Touch Type: Multi-Touch Projected Capacitive
- Front Panel Rating: Not Rated
- Color: Black
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 220
- Aspect Ratio: 16 : 9
- DisplayColors: 16.7 M
- Contrast Ratio: 1000:1
- Backlight: LED
- 9-36VDC Power Input

- Connectivity
- DisplayPort In: 1
- HDMI In: 1

Chassis Specifications:**General**

- Form Factor: NUC Box
- Front Facing I/O
- Color: Black
- Material: Steel & Plastic
- Material Thickness: 1mm

Front Ports

- USB 3.2 Ports (Front): 1

- RS232 COM Ports (Front): 1

Physical

- Depth: 109mm
- Depth (Inches): 4.295
- Width: 129mm
- Height: 34mm
- Shipping Box - Depth:
- Shipping Box - Width:
- Shipping Box - Height:
- Shipping Weight:

Power

- Built-in Chassis Power Supply: 9V - 24V DC In Jack



Simplifying Computing™

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525