

## 5U Rack Mount Workstation Rackmount

Configuration Number: BASE CONFIG  
SL-5U-W790SAGE-ST



### Type:

- 5U Rack Mount Workstation
- Depth: 20.87", Max Card Depth: Length: 455mm (without installing front fans and radiators)"

### Motherboard:

- Featuring Intel W790 Chipset and Intel Socket LGA4677 for Xeon W-3400 Series processor
- **Full Height Slots:**  
7 - PCIe x16
- **LAN:** 2x Ports (10GbE + 10GbE + IPMI)
- **RAID:** 0,1,5,10 and NVMe 0,1,5 RAID Intel VROC
- **Video:** VGA
- **Audio:** 8-Channel High Definition Audio CODEC Realtek ALC S1220A
- **Ports:**  
6x USB 2.0 Ports ( 2 Rear, 4 Internal Headers )  
2x USB 3.2 Gen 1 Ports ( 2 Front )  
4x USB 3.2 Gen 2 Ports ( 4 Rear )  
2x USB 3.2 Gen 2 Type-C Ports ( 1 Rear, 1 Internal Headers )  
1x COM Port (RS232 Internal Headers)  
See specifications for more ports
- **Operating Temperature:** 0°C to 40°C (32°F to 104°F)

### Configuration summary:

- **Processor:** Intel Xeon W3-2425 W-2400 Series CPU (6 Core) - 3.0 GHz (Up to 4.4GHz) - 15MB Cache (156W)
- **Memory:** 4 x 16GB DDR5 4800MHz ECC Registered RAM

- **Hard Drive:** 1TB PCIe 4.0 NVMe SSD M.2 7,450/6,900MB/s - Samsung 990 PRO
- **Power Supply:** 850W ATX12V / EPS12V Full Modular Power Supply - 80+ Gold Certified
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### Motherboard Model

- Motherboard Type: SSI EEB

### Supported CPU

- Number of Processors: 1
- Processor Type: Intel Socket LGA4677 for Xeon W-3400 Series

### Chipset

- Chipset: Intel W790 Chipset

### Memory

- Memory Type: DDR5 4800MHz ECCR
- Memory Type: ECC Registered
- DIMMS: 8
- Maximum Memory: 2048GB

### On Board Audio

- Audio Type: 8-Channel High Definition Audio CODEC Realtek ALC S1220A

### On Board Video

- Video Chipset: ASPEED AST2600 BMC
- Video on IO: VGA
- VGA Port Out: 1

### LAN

- LAN Ports: 2
- LAN Type: 10GbE + 10GbE + IPMI
- LAN Chipset: Intel 10Gb Ethernet
- Second LAN Chipset: Intel 10Gb Ethernet
- Wireless LAN: No Integrated WLAN

### Drive Interface

- SATA III Ports (6GB): 8
- RAID
- RAID Type: Hardware RAID

## Chassis Specifications:

### General

- Form Factor: 5U Rackmount
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: SSI EEB
- Redundant Power Supply Capable
- Slide Rails: Optional

### Expansion

- Full Height Slots: 8
- Max Card Depth: Length: 455mm (without installing front fans and radiators)"
- Internal 3.5" Bays: 4
- Internal 2.5" Bays: 4

### Front Ports

- USB 3.2 Ports (Front): 2
- USB Type-C (Front): 1

### Cooling System

- Maximum Fan Count: 6
- Included Fans: 3

### Physical

- Depth: 20.87"
- Width: 17.30"
- Height: 8.66"
- Shipping Weight: 71lbs

### Other Features

- Features:
  - Expansion card Length: 455mm (without installing front fans and radiators)
  - Width w/ expansion card

- RAID Levels Supported on Motherboard: 0, 1, 5, 10

### Expansion Slots

- PCI Express x16 Slots On Motherboard: 7

### M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 3
- M.2 Slot #1 Specs
  - PCIe Signal
  - 2242 - 22 mm x 42 mm.
  - 2260 - 22 mm x 60 mm.
  - 2280 - 22 mm x 80 mm.
  - 22110 - 22 mm x 110 mm.
- M.2 Slot #2 Specs
  - PCIe Signal
  - 2242 - 22 mm x 42 mm.
  - 2260 - 22 mm x 60 mm.
  - 2280 - 22 mm x 80 mm.
  - 22110 - 22 mm x 110 mm.
- M.2 Slot #3 Specs
  - PCIe Signal
  - 2242 - 22 mm x 42 mm.
  - 2260 - 22 mm x 60 mm.
  - 2280 - 22 mm x 80 mm.
  - 22110 - 22 mm x 110 mm.

### Rear IO

- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 4
- USB 3.2 Gen 2 Type C Ports (on I/O): 1
- USB 3.2 Gen 2x2 Type C Ports (on I/O): 1
- SPDIF Connector: 1
- Audio on IO

### Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.2 Gen 2 Type-C (on Headers): 1
- Serial (via Headers): 1
- FAN Connectors: 7
- Chassis Intrusion
- TPM Support: Via 2.0 Header

### Management Features

- Watch Dog

### Environmental

- Operating Temperature: 0°C to 40°C (32°F to 104°F )
- High Humidity: 85%
- Low Humidity: 10%

retainer: 157mm

Width w/o expansion

card retainer: 198mm

Limitation of Height w/

CPU cooler expansion

card

retainer:

181mm

Height w/o

expansion

card

retainer:

192mm

Limita 160m

tion m~19

of 0mm

PSU (Rem

oval

of

3.5"

drive

cage

elimin

ates

PSU

depth

limita

tion)

Dime

nsion

Incl.

rear

fan

cage:

440m

m

(W) x

220m

m (H)

x

530m

m

(D),

51.3

liters

Excl.

rear

fan

cage:

440m

### Operating System Support

- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC High End
- LINUX Ubuntu Desktop

### Compliance of Component

- CE
- RoHS
- FCC

### Other Features

- Other Features:  
Intel Xeon W-3400 Series Processors\*  
7 x PCIe 5.0 slot(s) (Seven at x16/x16/x16/x16/x16/x8/x16)\*\*  
Intel Xeon W-2400 Series Processors\*  
4 x PCIe 5.0 slot(s) (Four at x16/x16/x16/x16)\*\*  
\* Please check the PCIe bifurcation table on the support site  
(<https://www.asus.com/support/FAQ/1037507/>).  
\*\* Please refer to the block diagrams in the Appendix for more details.  
- To ensure compatibility of the device installed, please refer to <https://www.asus.com/support/> for the list of supported peripherals.

Total supports 3 x M.2 slots, 2 x SlimSAS slots and 8 x SATA 6Gb/s ports\*

Intel Xeon W-3400 Series Processors

M.2\_1 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 5.0 x4 mode)\*\*\*

M.2\_2 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 5.0 x4 mode)\*\*\*

Intel W790 Chipset\*\*

M.2\_3 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 4.0 x4 mode)

SlimSAS\_1 port supports PCIe 4.0 x4 mode NVMe device

SlimSAS\_2 port supports PCIe 4.0 x4 mode NVMe device

8 x SATA 6Gb/s ports

\* Supports Intel Virtual RAID on CPU (Intel VROC) and Intel Volume Management Device (IntelVMD)

\*\* Intel VROC Technology supports PCIe RAID 0/1/5/10, SATA RAID 0/1/5/10. VROC\_HW\_Key is purchased separately.

\*\*\* M.2\_1 and M.2\_2 slots will be disabled once an

m  
(W) x  
220m  
m (H)  
x  
485m  
m  
(D),  
46.95  
liters  
Incl.  
rear  
fan  
cage:  
17.3"  
(W),  
8.66"  
(H),  
20.87  
" (D)  
Excl.  
rear  
fan  
cage:  
17.3"  
(W),  
8.66"  
(H),  
19.1"  
(D)

- Chassis Warranty: 1 Year

Intel Xeon W-2400 Series Processor is installed.

\* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year



[www.superlogics.com](http://www.superlogics.com)  
Phone: 1-508-650-9500

[sales@superlogics.com](mailto:sales@superlogics.com)  
Fax: 1-508-650-9525