

# Microbox PC Embedded PC

Configuration Number: BASE CONFIG  
SL-EB-LLN100EM-S18



## Type:

- Microbox PC
- Dimension: 2.60" x 12.30" x 8.27"

## Motherboard:

- Featuring Intel Celeron SoC and Intel Quad-core Processor N100 (up to 3.4 GHz)
- **Long Production Cycle Motherboard (Through Q1 2026)**
- **LAN:** 2x Ports (1GbE + 1GbE)
- **Video:** VGA + HDMI
- **Audio:** Realtek ALC897
- **Ports:**
  - 3x USB 2.0 Ports ( 1 Front, 2 Rear )
  - 4x USB 3.2 Gen 1 Ports ( 2 Rear, 2 Internal Headers )
  - 6x COM Ports ( 2 RS232 Rear, 3 RS232 Internal Headers, 1 RS232/422/485 Rear)

See specifications for more ports
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

## Configuration summary:

- **Memory:** 8GB DDR4 3200MHz SODIMM RAM
- **Hard Drive:** 500GB M.2 2280 NVMe SSD or greater
- **Power Supply:** AC/DC Power Adapter Included
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

# Technical Specifications

## MotherBoard Specifications:

### Motherboard Model

- Motherboard Type: MiniITX
- Fanless
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2026

### Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Quad-core Processor N100 (up to 3.4 GHz)

### Chipset

- Chipset: Intel Celeron SoC

### Memory

- Memory Type: DDR4 3200MHz
- Memory Type: Non-ECC
- DIMMS: 1
- Maximum Memory: 16GB

### On Board Audio

- Audio Type: Realtek ALC897

### On Board Video

- Video Chipset: Supported by CPU - see Embedded CPU Information
- Video on IO: VGA + HDMI
- VGA Port Out: 1
- HDMI Out: 1

### LAN

- LAN Ports: 2
- LAN Type: 1GbE + 1GbE
- LAN Chipset: Realtek RTL8111H
- Second LAN Chipset: Realtek RTL8111H
- Wireless LAN: No Integrated WLAN

### Drive Interface

- SATA III Ports (6GB): 2

### M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs
- PCIe Signal

## Chassis Specifications:

### General

- Form Factor: Micro PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX
- Slide Rails: Optional

### Expansion

- Full Height Slots: 1
- Max Card Depth: 7.5"
- Internal 2.5" Bays: 2
- Serial Port Punchouts: 3
- Parallel Port Punchouts: 1
- Antennae Punchout: 2

### Front Ports

- USB 2.0 Ports (Front): 2

### Cooling System

- Maximum Fan Count: 2

### Physical

- Depth: 2.60"
- Depth (Inches): 2.6
- Width: 12.30"
- Height: 8.27"
- Shipping Box - Depth: 16"
- Shipping Box - Width: 16"
- Shipping Box - Height: 8"
- Shipping Weight: 11lbs

### Other Features

- Chassis Warranty: 1 Year

### Power

- Built-in Chassis Power Supply: AC/DC Power Adapter Included

- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.
- M.2 E-Key Slot
- PCIe Signal
- USB
- 2230 - 22 mm x 30 mm.

#### **Rear IO**

- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- Serial (Rear IO): 2
- Serial 232/422/485 Ports: 1
- Audio on IO

#### **Headers**

- USB 2.0 Ports (on Headers): 1
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 3
- FAN Connectors: 1
- LVDS
- Chassis Intrusion
- TPM Support: Via 2.0 Header
- DC Power: 12V DC-in

#### **Environmental**

- Operating Temperature: 0°C to 60°C (32°F to 140°F )
- High Humidity: 95%
- Low Humidity: 10%

#### **Operating System Support**

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT 2021 LTSC Entry
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 IoT 2024 LTSC Entry
- LINUX Ubuntu Desktop

#### **Compliance of Component**

- FCC

#### **Other Features**

- Features:

Expansion slots

1x PCI Express 3.0/2.0 x1 slot (x1 mode)

1x M.2 Socket 1 with E key, type 2230 for WIFI/BT device (PCIe x1 /USB2.0)

1x M.2 Socket 3 with M key, type 2242/ 2260/

2280 (SATA/PClex1)

- Motherboard Warranty: 1 Year



[www.superlogics.com](http://www.superlogics.com)  
Phone: 1-508-650-9500

[sales@superlogics.com](mailto:sales@superlogics.com)  
Fax: 1-508-650-9525