

1U Rack Mount Server Rackmount

Configuration Number: BASE CONFIG
SL-1U-LLQ670E-IR2



Type:

- 1U Rack Mount Server
- Depth: 15.48"

Motherboard:

- Featuring Intel Q670 Chipset and 13th & 12th Gen Intel Core™, Pentium Gold and Celeron processor
- **Long Production Cycle Motherboard (Through Q1 2029)**
- **LAN:** 3x Ports (2.5GbE + 2.5GbE + 1GbE)
- **RAID:** 0,1 and NVMe 0,1
- **Video:** DisplayPort
- **Audio:** Realtek ALC897
- **Ports:**
 - 4x USB 2.0 Ports (4 Internal Headers)
 - 4x USB 3.2 Gen 1 Ports (2 Front, 2 Rear)
 - 3x USB 3.2 Gen 2 Ports (3 Rear)
 - 1x USB 3.2 Gen 2 Type-C Port (1 Rear)
 - 10x COM Ports (9 RS232 Internal Headers, 1 RS232/422/485 Rear)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

Configuration summary:

- **Processor:** i3-12100 - 3.30GHz (up to 4.30GHz) Intel Core CPU - 4 Core, 12MB Cache, UHD Graphics 730 (Base 60W, Max 89W) (ERM)
- **Memory:** 8GB DDR5 4800MHz RAM Non-ECC Unbuffered DIMM
- **Hard Drive:** 250GB NVMe SSD M.2 2.9GB/1.3GB - Samsung 980
- **Power Supply:** 315W
- **Operating System:** Not Included -

- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MicroATX
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2029

Supported CPU

- Number of Processors: 1
- Processor Type: 13th & 12th Gen Intel Core™, Pentium Gold and Celeron

Chipset

- Chipset: Intel Q670 Chipset

Memory

- Memory Type: DDR5 4800MHz
- Memory Type: Non-ECC
- DIMMS: 4
- Maximum Memory: 128GB

On Board Audio

- Audio Type: Realtek ALC897

On Board Video

- Video Chipset: Supported by CPU - depends on CPU selected
- Video on IO: DisplayPort
- Display Port Out: 4

LAN

- LAN Ports: 3
- LAN Type: 2.5GbE + 2.5GbE + 1GbE
- LAN Chipset: Intel i226-V 2.5GbE Ethernet
- Second LAN Chipset: Intel i226-LM 2.5GbE Ethernet
- Third LAN Chipset: Intel i210AT
- Wireless LAN: No Integrated WLAN

Drive Interface

- SATA III Ports (6GB): 7

M.2 Slot Specs

- Total M.2 NVMe SSD Slots: 1
- M.2 Slot #1 Specs

Chassis Specifications:

General

- Form Factor: 1U Rackmount
- Color: Black & Silver
- Material: SGCC
- Material Thickness: 1mm
- Motherboard Compatibility: ATX
- Slide Rails: Optional

Expansion

- Full Height Slots: 1
- Internal 3.5" Bays: 1
- 2.5" Hot Swap Bays: 2

Front Ports

- USB 3.2 Ports (Front): 2

Cooling System

- Maximum Fan Count: 3
- Included Fans: 2

Physical

- Depth: 15.48"
- Depth (Inches): 15.48
- Width: 16.93"
- Height: 1.71"
- Shipping Box - Depth: 592mm
- Shipping Box - Width: 518mm
- Shipping Box - Height: 155mm
- Shipping Weight: 12lbs

Other Features

- Features:
 - Full height PCIe slot x 1 (via riser card and bracket)
 - External: slim ODD x 1, hot-swap 2.5" x 2
 - Internal: 3.5" HDD x 1

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: 315W
- Remote Server Management:

- M.2 SATA SSD
- PCIe Signal
- 2242 - 22 mm x 42 mm.
- 2260 - 22 mm x 60 mm.
- 2280 - 22 mm x 80 mm.

Rear IO

- USB 3.2 Gen 1 Type A Ports (on IO): 2
- USB 3.2 Gen 2 Type A Ports (on IO): 3
- USB 3.2 Gen 2 Type C Ports (on I/O): 1
- Serial 232/422/485 Ports: 1
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- USB 3.0 Type A Internal: 1
- Serial (via Headers): 9
- FAN Connectors: 4
- Digital I/O (8 Bit) On Headers
- Audio on Headers
- Chassis Intrusion
- TPM Support: Via 2.0 Header

Management Features

- Watch Dog

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 95%
- Low Humidity: 10%

Operating System Support

- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- Windows 11 Home (64 Bit)
- Windows 11 Pro (64 Bit)
- Windows 11 Pro for WS (64 Bit)
- Windows 11 IoT 2024 LTSC Value
- Windows 11 IoT 2024 LTSC High End
- RED HAT Enterprise LINUX WORKSTATION STANDARD
- RED HAT Enterprise LINUX SERVER BASIC
- RED HAT Enterprise LINUX SERVER STANDARD
- LINUX Ubuntu Desktop
- Ubuntu Server Edition

Compliance of Component

- CE

- FCC

Other Features

- Features:

PCIe Expansion Slots

1x PCIe 5.0 x16 Slot 1 x16 mode/ 2 x8 mode)

1x PCIe 4.0 x4 Slot (x4 mode)

1x PCIe 5.0 x16 Slot (x8 mode)

1x PCIe 4.0 x4 Slot (x4 mode)

1x M.2 E key, Type 2230 for WIFI/BT device
(PCIex1 & USB2.0&CNVI)

1x M.2 M key, Type 2242/2260/2280 (PCIex4
/SATAmode) supports NVMe

- Motherboard Warranty: 1 Year



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525