

2U Rack Mount Industrial PC Rackmount

Configuration Number: BASE CONFIG

SL-2U-Q87SLQ-WF











Type:

- 2U Rack Mount Industrial PC
- Depth: 18", Max Card Depth: 12.25", Locking Front Bezel

Motherboard:

- Featuring Intel Q87 Chipset and 4th Gen Core i3/i5/i7 (LGA1150, 'Haswell') processor
- Long Production Cycle Motherboard (Through Q4 2022)
- **LAN:** 2x Ports (1GbE + 1GbE)
- **RAID:** 0,1,5,10
- Video: HDMI + DisplayPort + VGA + DVI-
- Audio: 7.1 Channel HD Audio by Realtek ALC888S
- Ports:

8x USB 2.0 Ports (4 Rear, 4 Internal Headers)

4x USB 3.2 Gen 1 Ports (2 Front, 2 Rear) 4x COM Ports (3 RS232 Internal Headers, 1 RS232/422/485 Internal Headers) See specifications for more ports

• Operating Temperature: 0°C to 60°C (32°F to 140°F)

Configuration summary:

- Processor: G1820 2.7GHz Intel Dual Core Celeron CPU - 2MB Cache, HD Graphics (53W) (ERM)
- **Memory:** 4GB DDR3 1600MHz RAM
- Hard Drive: 1.0TB SATA 6.0Gb/s 7200RPM 64MB 3.5" - WD Blue
- Power Supply: 400W Power Supply
- Operating System: Not Included -

Technical Specifications

MotherBoard Specifications:

Motherboard Model

Motherboard Type: MicroATX

Long Life: YESEOL Date: Q4 2022

Supported CPU

• Number of Processors: 1

 Processor Type: 4th Gen Core i3/i5/i7 (LGA1150, 'Haswell')

Chipset

• Chipset: Intel Q87 Chipset

Memory

• Memory Type: DDR3 1600MHz

Memory Type: Non-ECC

• DIMMS: 4

Maximum Memory: 32GB

On Board Audio

 Audio Type: 7.1 Channel HD Audio by Realtek ALC888S

On Board Video

• Video Chipset: Intel HD Graphics 4600

• Video on IO: HDMI + DisplayPort + VGA + DVI-D

VGA Port Out: 1DVI-D Out: 1Display Port Out: 1

• HDMI Out: 1

LAN

• LAN Ports: 2

LAN Type: 1GbE + 1GbELAN Chipset: Intel i217LM

Second LAN Chipset: Intel i210ATWireless LAN: No Integrated WLAN

Drive Interface

• SATA III Ports (6GB): 5

RAID

• RAID Type: Software RAID

• RAID Levels Supported on Motherboard: 0, 1, 5,

Chassis Specifications:

General

• Form Factor: 2U Rackmount

Color: Black & SilverMaterial: Metal/SteelMaterial Thickness: 1mm

• Motherboard Compatibility: ATX

• Slide Rails: Optional

Expansion

Full Height Slots: 3Max Card Depth: 12.25"External 5.25" Bays: 1

Internal 3.5" Bays: 2External 3.5" Bays: 1

• Internal 2.5" Bays: 1

Front Ports

• USB 3.2 Ports (Front): 2

Cooling System

• Maximum Fan Count: 3

• Included Fans: 1

Physical

• Depth: 18"

Depth (Inches): 18Width: 16.90"

• Height: 3.50"

Shipping Box - Depth: 20"Shipping Box - Width: 40"

• Shipping Box - Height: 40"

• Shipping Weight: 35lbs

Compliance of Component

RoHS

Other Features

• Chassis Warranty: 1 Year

Mini PCle

- mini PCle
- mSATA
- half and/or full size mini PCle card: full/half size
- mSATA

Rear IO

- PS/2 Combo (Mouse/Keyboard)
- USB 2.0 Ports (on IO): 4
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 3
- Serial 232/422/485 Ports: 1
- FAN Connectors: 4
- Audio on Headers
- DOM
- PS/2 Combo (Mouse/Keyboard) on Headers
- Chassis Intrusion
- TPM Support: Via 1.2 Header

Management Features

- AMT
- vPRO
- NMI
- Watch Dog

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (32-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- SL-Windows 10PRO to 7PRO 32-bit
- SL-Windows 10PRO to 7PRO 64-bit
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows 8.1 (32-bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (32-bit)
- Windows 8.1 Pro (64-bit)
- Windows Embedded 8 (32-bit)

- Windows Embedded 8 (64-bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 Pro WS (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Value
- Windows 10 IoT Ent
- Windows 10 IoT Value 2019 LTSC
- Windows 10 IoT Ent 2019 LTSC
- Windows 10 IoT 2021 LTSC Value
- Windows 10 IoT 2021 LTSC High End
- LINUX Ubuntu Desktop

Compliance of Component

• RoHS

Other Features

- Other Features:
 - 1x PCI-E 3.0 x16 (in x16) slot
 - 1x PCI-E 2.0 x4 slot
 - 1x PCI-E 2.0 x1 slot
 - 1x Mini-PCI-E w/ mSATA support
 - * Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

• Motherboard Warranty: 1 Year



www.superlogics.com Phone: 1-508-650-9500 sales@superlogics.com Fax: 1-508-650-9525