

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-24P-LL2930A-S29



Desktop Touchscreen.

Type:

- Fanless Panel PC
- **Screen:**
 - 24" Multi-Touch Projected Capacitive, Native Resolution: 1920 x 1080, Front Panel Rating: Not Rated

Motherboard:

- Featuring Intel Celeron SoC and Intel Celeron N2930 Processor (1.83GHz Quad Core, Burst 2.16GHz) TDP 7.5W
- **Long Production Cycle Motherboard (Through Q1 2028)**
- **No Available Slots**
- **LAN:** 1x Ports (1GbE (10/100/1000))
- **Video:** VGA + HDMI
- **Audio:** 5.1 channel by Realtek ALC662
- **Ports:**
 - 6x USB 2.0 Ports (2 Front, 2 Rear, 2 Internal Headers)
 - 4x USB 3.2 Gen 1 Ports (2 Rear, 2 Internal Headers)
 - 5x COM Ports (4 RS232 Internal Headers, 1 RS232/422/485 Internal Headers)
 - 1x Parallel Port (Headers)
- **Operating Temperature:** 0°C to 60°C (32°F to 140°F)

Configuration summary:

- **Memory:** 4GB DDR3L 1600MHz SODIMM RAM 1.35V
- **Hard Drive:** 256GB mSATA SSD SATA

6.0Gb/s, 550/500MB/s read/write (or greater)

- **Power Supply:** AC/DC Power Adapter Included
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: MiniITX
- Fanless
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2028

Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Celeron N2930 Processor (1.83GHz Quad Core, Burst 2.16GHz) TDP 7.5W

Chipset

- Chipset: Intel Celeron SoC

Memory

- Memory Type: SO DIMM DDR3 1333MHz
- Memory Type: Non-ECC
- DIMMS: 2
- Maximum Memory: 8GB

On Board Audio

- Audio Type: 5.1 channel by Realtek ALC662

On Board Video

- Video Chipset: Intel 7th generation (Gen 7) Graphics
- Video on IO: VGA + HDMI
- VGA Port Out: 1
- HDMI Out: 1

LAN

- LAN Ports: 1
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Realtek 8111DL
- Wireless LAN: No Integrated WLAN

Display Specifications

Display

- Screen Size (inches): 24
- Touch Type: Multi-Touch Projected Capacitive
- Aspect Ratio: 16:9
- Native Display Resolution: 1920 x 1080
- Brightness (nits): 250
- Screen Refresh Rate: 60Hz
- Display Area (H): 11.70"
- Display Area (V): 20.70"
- Aspect Ratio: 16:9
- DisplayColors: 16.7 M
- Contrast Ratio: 3,000:1
- Backlight: LED
- Viewing Angle(U) : 178°
- Viewing Angle(D) : 178°
- Viewing Angle(L) : 178°
- Viewing Angle(R) : 178°

Connectivity

- VGA Port In: 1
- HDMI In: 1
- Display Port In: 1

Mounting Options

- Mounting Options: VESA 100mm x 100mm, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width: 21.60"
- Height: 15.80"
- Depth: 7.80"
- Unboxed Weight: 5.7lbs
- Shipping Weight: 15.8lbs

Environmental

Drive Interface

- SATA II Ports (3GB): 2

Expansion Slots

- PCI Express x1 Slots On Motherboard: 1

Mini PCIe

- mini PCIe
- mSATA
- USB and PCIe signals (Internal)
- half and/or full size mini PCIe card: full size
- half and/or full size mini PCIe card: half size

M.2 Slot Specs

Rear IO

- USB 2.0 Ports (on IO): 2
- USB 3.2 Gen 1 Type A Ports (on IO): 2
- Audio on IO

Headers

- USB 2.0 Ports (on Headers): 4
- USB 3.2 Gen 1 Ports (on Headers): 2
- Serial (via Headers): 4
- Serial 232/422/485 Ports: 1
- Parallel Ports: 1
- FAN Connectors: 3
- Digital I/O (8 Bit) On Headers
- Audio on Headers
- LVDS

Environmental

- Operating Temperature: 0°C to 60°C (32°F to 140°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (32-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- Windows 7 PRO (FES) DGS 32-BIT
- Windows 7 PRO (FES) DGS 64-BIT
- SL-Windows 10PRO to 7PRO 32-bit
- SL-Windows 10PRO to 7PRO 64-bit
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows 8.1 (32-bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (32-bit)
- Windows 8.1 Pro (64-bit)

- MTBF:
- Maximum Operating Temperature: 104F
- Low Operating Temp: 32F
- High Humidity: 90%
- Low Humidity: 20%
- Storage Temp (High):
- Storage Temp (Low):
- Storage Humidity (High):
- Storage Humidity (Low):

Power

- Power Supply: AC 100~240V/12V DC
- Power Consumption (on): 26Watts

Compliance of Component

- CE
- RoHS
- FCC
- CB

Warranty

- Warranty: 1 year

Other

- Features:

24" Frameless Touch Monitor with 10 Points PCAP

- Touch function for wet hands and multiple types of glove
- Pen clicks & Palm rejection technology
- 4-sides frameless design and optional stand for flexibility
- Friendly touch mode setting
- Intuitive touch OSD with ViewSonic Touch Controller

- Windows Embedded 8 (32-bit)
- Windows Embedded 8 (64-bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- SL-Windows 11PRO to 10PRO 64bit
- Windows 10 IoT Entry
- Windows 10 IoT Entry 2019 LTSC
- Windows 10 IoT 2021 LTSC Entry

Compliance of Component

- UL
- CE
- RoHS
- FCC

Other Features

- Other Features:
1x PCI Express 2.0 x1 Slot

* Access to PCI Express slot requires expansion slot and a riser in some chassis models. Please check Chassis Specification section for more information.

If you have any questions, please discuss with our Sales Engineers.

- Motherboard Warranty: 1 Year

Chassis Specifications:

General

- Form Factor: Embedded PC
- Color: Black
- Material: Metal/Steel
- Material Thickness: 1mm
- Motherboard Compatibility: Mini ITX
- Slide Rails: Optional

Expansion

- Internal 2.5" Bays: 1
- Serial Port Punchouts: 3
- Parallel Port Punchouts: 1

Front Ports

- USB 2.0 Ports (Front): 2

Physical

- Depth: 193mm
- Depth (Inches): 7.6
- Width: 215mm
- Height: 45mm
- Shipping Box - Depth: 13"

- Shipping Box - Width: 9"
- Shipping Box - Height: 5"
- Shipping Weight: 5lbs

Other Features

- Chassis Warranty: 1 Year

Power

- Built-in Chassis Power Supply: AC/DC Power Adapter Included



www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525