

HMI Panel PC Panel PC

Configuration Number: BASE CONFIG
SL-PPC-10AW-N2930-H-2LAN



LCD requires 12VDC power supply (included), Separate Computer input is wide voltage input

Type:

- Fanless Panel PC
- **Screen:**
 - 10" 5-Wire Resistive, Native Resolution: 1280 x 800, Front Panel Rating: IP65 / NEMA4
- **Mounting:** Bezel Mounting Hardware Included, Suitable for Mounting in Cut-Out

Motherboard:

- Featuring Intel Celeron SoC and Intel Celeron N2930 Processor (1.83GHz Quad Core, Burst 2.16GHz) TDP 7.5W
- **Long Production Cycle Motherboard (Through Q1 2029)**
- **LAN:** 2x Ports (1GbE (10/100/1000))
- **WiFi:** Integrated Realtek 802.11 b/g/n Wireless LAN - Removable Under Networking Section
- **Video:** HDMI
- **Audio:** Realtek ALC888 HD Audio
- **Ports:**
 - 3x USB 2.0 Ports (1 Front, 2 Rear)
 - 1x COM Port (RS232/422/485 Rear)
 - See specifications for more ports
- **Operating Temperature:** 0°C to 40°C (32°F to 104°F)

Configuration summary:

- **Memory:** 4GB DDR3L 1600MHz SODIMM RAM 1.35V
- **Hard Drive:** 256GB mSATA SSD SATA

6.0Gb/s, 550/500MB/s read/write (or greater)

- **Power Supply:** AC_90~240V / DC_12V_3A/36W. 12VDC 36W External Power Adapter
- **Operating System:** Not Included -
- **Warranty:** One-Year Depot Warranty

Technical Specifications

MotherBoard Specifications:

Motherboard Model

- Motherboard Type: NUC (101x101 mm)
- Long Production Cycle
- Long Life: YES
- EOL Date: Q1 2029
- Fanless

Supported CPU

- Number of Processors: 1
- Processor Type: Embedded CPUs (ultra-low power, soldered down)
- Embedded CPU: Intel Celeron N2930 Processor (1.83GHz Quad Core, Burst 2.16GHz) TDP 7.5W

Chipset

- Chipset: Intel Celeron SoC

Memory

- Memory Type: SO DIMM DDR3 1600MHz
- Memory Type: Non-ECC
- DIMMS: 1
- Maximum Memory: 8GB

On Board Audio

- Audio Type: Realtek ALC888 HD Audio

On Board Video

- Video Chipset: Intel HD Graphics
- Video on IO: HDMI
- HDMI Out: 1

LAN

- LAN Ports: 2
- LAN Type: 1GbE (10/100/1000)
- LAN Chipset: Intel i211AT
- Second LAN Chipset: Intel i211AT
- Wireless LAN: Integrated Realtek 802.11 b/g/n

Display Specifications

Display

- Screen Size (inches): 10
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Aspect Ratio: 16 : 9
- Native Display Resolution: 1280 x 800
- Brightness (nits): 300
- Screen Refresh Rate: 60Hz
- Display Area (H): 216.96mm
- Display Area (V): 135.60mm
- Aspect Ratio: 16 : 9
- DisplayColors: 16.2 M
- Contrast Ratio: 800:1
- Backlight: LED
- Viewing Angle(U) : 80
- Viewing Angle(D) : 80
- Viewing Angle(L) : 80
- Viewing Angle(R) : 80

Connectivity

- HDMI In: 1
- Display Port In: 1
- Touchscreen Interface USB Port (Front): 1

Mounting Options

- Mounting Options: Bezel Mounting Hardware Included, Other options sold separately
- Suggested Cut-Out Dimension (Width):
- Suggested Cut-Out Dimension (Height):

Physical

- Width:
- Height:
- Depth:
- Depth (Inches): [Click Available Downloads Tab >](#)

Wireless LAN - Removable Under Networking Section

Expansion Slots

- mini PCIe
- mSATA
- half and/or full size mini PCIe card: full size
- USB and PCIe signals (Internal)
- half and/or full size mini PCIe card: half size

Rear IO

- USB 2.0 Ports (on IO): 2
- Serial 232/422/485 Ports: 1
- SPDIF Connector: 1

Headers

- USB 2.0 Ports (on Headers): 1

Environmental

- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- High Humidity: 90%
- Low Humidity: 5%

Operating System Support

- Windows 7 Ultimate (64-bit)
- Windows 7 Pro (32-bit)
- Windows 7 Pro (64-bit)
- Windows 7 Pro (FES) 32-Bit
- Windows 7 Pro (FES) 64-Bit
- Windows Embedded 7 (32-Bit)
- Windows Embedded 7 (64-Bit)
- Windows 8.1 (32-bit)
- Windows 8.1 (64-bit)
- Windows 8.1 Pro (32-bit)
- Windows 8.1 Pro (64-bit)
- Windows 10 Home (64 Bit)
- Windows 10 Pro (64-Bit)
- Windows 10 IoT Entry
- Windows 10 IoT Entry 32-bit 2019 LTSC
- Windows 10 IoT Entry 2019 LTSC
- SL-Windows 11PRO to 10PRO 64bit

Compliance of Component

- UL
- CE
- RoHS
- FCC
- CCC

Warranty of Component

- Motherboard Warranty: 1 Year

Mechanical Drawings.

- Unboxed Weight: 6lbs
- Shipping Weight: 25lbs

Environmental

- MTBF: 30000hours
- Maximum Operating Temperature: 50C
- High Humidity: 90%
- Low Humidity: 8%
- Storage Temp (High): 60C
- Storage Temp (Low): -20C
- Storage Humidity (High): 90%
- Storage Humidity (Low): 8%

Power

- Power Supply: AC 100~240V/12V DC

Compliance of Component

- CE
- CCC

Warranty

- Warranty: 1 year

Other

- Built-in Chassis Power Supply: Wide Voltage Input (9-36VDC)

- Features:

ETA mid-June 2018

Industrial Display

- Screen Size: 10"
- Touch Type: 5-Wire Resistive
- Front Panel Rating: IP65 / NEMA4
- Native Display Resolution: 1280 x 800
- Brightness (nits): 300
- Wide Voltage Input (9-36VDC)

Chassis Specifications:

General

- Form Factor: Micro PC
- Color: Black
- Material: Metal/Aluminum
- Material Thickness: 1mm

Front Ports

- USB 2.0 Ports (Front): 1
- USB 3.2 Ports (Front): 1

Cooling System

- Maximum Fan Count: 1
- Included Fans: 1

Physical

- Depth: 116mm
- Depth (Inches): 4.5
- Width: 110mm
- Height: 49mm
- Shipping Box - Depth: 4"
- Shipping Box - Width: 10"
- Shipping Box - Height: 8"
- Shipping Weight: 6lbs

Power

- Built-in Chassis Power Supply: AC_90~240V / DC_12V_3A/36W. 12VDC 36W External Power Adapter



Simplifying Computing™

www.superlogics.com
Phone: 1-508-650-9500

sales@superlogics.com
Fax: 1-508-650-9525